

GUÍA DE SELECCIÓN DE EQUIPOS DE APLICACIÓN



		Ultimate MX II 695 ProContractor Series	Ultimate MX II 490 PC Pro	Nova 390 PC	190 Express PC	Boquillas Recomendadas, tamaño de orificio en pulgadas
Látex	Loxon XP	●	●			0.019 - 0.023
	SuperPaint	●	●			0.017 - 0.021
	Exterior Accents	●	●			0.017 - 0.021
	ColorAccents	●	●			0.017 - 0.021
	Shertech 6000	●	●	●		0.017 - 0.021
	Excello	●	●	●		0.015 - 0.021
	Shertech 4000	●	●	●	●	0.015 - 0.019
	Colonial	●	●	●	●	0.015 - 0.019
	Peninsular	●	●	●	●	0.015 - 0.017
	Colorámica	●	●	●	●	0.015 - 0.017
Selladores	Builders Base (Base Agua)	●	●	●	●	0.015 - 0.019
	Builders Solution (Base Solvente)		●	●	●	0.015 - 0.019
Impermeabilizantes	Aqualock 8000	●	●			0.021 - 0.023
	Aqualock 6000	●	●	●		0.021 - 0.023
	Aqualock 4000	●	●	●	●	0.017 - 0.021
	Aqualock Bloqueador de Agua	●	●	●		0.021 - 0.023
Anticorrosivos	Macropoxy 646 FC	●				0.017 - 0.023
	Kem Cati Coat	●				0.017 - 0.023
	Kem Kromik Univeral HS	●				0.017 - 0.021
	Kem Faster Dry	●	●			0.015 - 0.021
	Builders Base Anticorrosivo 6000 Rustop	●	●	●	●	0.013 - 0.017
	Builders Base Anticorrosivo 4000 Colonial	●	●	●	●	0.013 - 0.017
	Builders Base Anticorrosivo 2000 Estructural	●	●	●	●	0.013 - 0.017
	Colorámica		●	●	●	0.013 - 0.017
Esmaltes	Kem Enamel Poliuretano Industrial	●	●	●	●	0.011 - 0.015
	Kem Lustral/Sistema 4000	●	●	●	●	0.011 - 0.015
	Kem Faster Dry	●	●	●	●	0.011 - 0.015
	Excello	●	●	●	●	0.011 - 0.015
	Colonial	●	●	●	●	0.011 - 0.015
	Peninsular	●	●	●	●	0.011 - 0.015
	Colorámica	●	●	●	●	0.011 - 0.013
Direct-to-Metal	Base Solvente	●	●	●	●	0.013 - 0.017
	Base Agua	●	●	●	●	0.013 - 0.017